

Package: hubCI (via r-universe)

September 1, 2024

Title Toolbox for hubverse Continuous Integration
Version 0.0.1
Description Functions for setting up hubverse Continuous Integration workflows.
License MIT + file LICENSE
Suggests covr, fs, testthat (>= 3.0.0)
Config/testthat/edition 3
Encoding UTF-8
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.1
Imports gh, purrr, rlang, usethis
URL <https://github.com/hubverse-org/hubCI>,
<https://hubverse-org.github.io/hubCI/>
BugReports <https://github.com/hubverse-org/hubCI/issues>
Config/Needs/website hubverse-org/hubStyle
Repository <https://hubverse-org.r-universe.dev>
RemoteUrl <https://github.com/hubverse-org/hubCI>
RemoteRef HEAD
RemoteSha 2dd49acd456d3bedab8a1b5944af6f19f5b52a5a

Contents

use_hub_github_action	2
Index	3

use_hub_github_action *Hubverse GitHub Action setup*

Description

Sets up common continuous integration (CI) workflows for a hub that is hosted on GitHub using **GitHub Actions**. Available actions are hosted in repository [hubverse-org/hubverse-actions](https://github.com/hubverse-org/hubverse-actions). The function creates the necessary directories and downloads the requested GitHub Action yaml file.

Usage

```
use_hub_github_action(name, ref = NULL)
```

Arguments

name	Name of workflow, i.e. the name of one of the action repository directories containing a GitHub Action workflow .yaml file.
ref	Desired Git reference, usually the name of a tag ("v0.1.0") or branch ("main"). Other possibilities include a commit SHA ("d1c516d") or "HEAD" (meaning "tip of remote's default branch"). If not specified, defaults to the latest published release of hubverse-org/hubverse-actions (https://github.com/hubverse-org/hubverse-actions/releases)

Examples

```
## Not run:  
use_hub_github_action(name = "validate-submission")  
  
## End(Not run)
```

Index

`use_hub_github_action`, 2